




Product Line Drawing



Input Parameters	
Input Voltage Range	220-240 Vac
Input Current	<0.03A
Power Factor	> 0.32
Frequency	50Hz
Ambient Temperature	0-40C
Class	II
Maximum Input Power (While Charging Battery)	1.7 W
Average Input Power (Not Charging Battery)	0.5 W

Emergency Parameters	
Emergency Duration	180minutes
Battery Code(s)	zc-batt-1B1-ACA
Battery Type	LiFePO4
Input Battery Voltage	2.0-4.0 Vdc
Output Battery Voltage	2.0-3.65 Vdc
Input Battery Current	650mA
Output Battery Current	150mA
Charging Time	24 hours
Emergency Output Power	1.55 W

Mechanical	
Product Dimension Height	130mm
Product Dimension Diameter	110mm


Standards	
IEC 60598-1	Yes
IEC 60598-2-22	Yes
IEC 62034	Yes

Packaging	
Carton Length	0..
Carton Width	0..
Carton Height	0..
Unit Net Weight	0.00kg
Carton Gross Weight	0.00..
EAN 13	
EAN 14	
Carton Quantity	Carton 12

Photometrics

Emergency Mode (Room Lens)

Emergency Mode (Room Lens)



Lumens	261.6
--------	-------

Emergency Mode (Room Lens) 0.5 lux



Mounting Height	0.5 lux	
2.5m	5.24	10.48
2.8m	5.62	11.23
3.0m	5.89	11.78
4.0m	7.22	14.43
5.0m	8.16	16.32


Emergency Mode (Room Lens) 1 lux



Mounting Height	1 lux			
2.5m	4.70	9.40	9.40	4.70
2.8m	5.05	10.10	10.10	5.05
3.0m	5.20	10.39	10.39	5.20
4.0m	6.04	12.09	11.22	5.61
5.0m	4.66	9.33	11.11	5.55

Emergency Mode (Corridor Lens)

Emergency Mode (Corridor Lens)



Lumens	260.2
--------	-------

Emergency Mode (Corridor Lens) 0.5 lux



Mounting Height	0.5 lux			
2.5m	6.69	13.37	6.64	3.32
2.8m	7.29	14.59	7.04	3.52
3.0m	7.62	15.23	7.28	3.64
4.0m	8.98	17.97	8.00	4.00
5.0m	10.25	20.50	8.24	4.12

Emergency Mode (Corridor Lens) 1 lux



Mounting Height	1 lux			
2.5m	6.04	12.07	5.46	2.73
2.8m	6.44	12.88	5.60	2.80
3.0m	6.58	13.17	5.69	2.85
4.0m	7.85	15.70	6.03	3.01
5.0m	8.66	17.32	6.01	3.00